

HELAIAN DATA KESELAMATAN SAFETY DATA SHEET

CONDUFAST

CONDUFAST

Bahagian 1: Pengenalan bahan kimia berbahaya dan pembekal

Pengecam produk : CONDUFAST
Cat. No. : 40100039
Saiz bekas : 1 kg
Cara mengenalpastian yang lain : Tidak tersedia.
Jenis Produk : Serbuk.

Kegunaan relevan yang dikenal pasti bagi zat atau campuran serta kegunaan yang tidak dinasihatkan

Kegunaan Produk : Untuk pembenaman spesimen materialografi
Kawasan Penggunaan : Aplikasi profesional.

Pembekal : Struers ApS
Pederstrupvej 84
DK-2750 Ballerup
Nombor telefon: +45 44 600 800

alamat e-mel orang yang bertanggungjawab terhadap SDS ini : sdsquestions@struers.dk
Nombor telefon kecemasan : 999 (24/7)

Section 1. Identification of the hazardous chemical and of the supplier

Product identifier : CONDUFAST
Cat. No. : 40100039
Container size : 1 kg
Other means of identification : Not available.
Product type : Powder.

Relevant identified uses of the substance or mixture and uses advised against

Product use : For embedding of materialographic specimens
Area of application : Professional applications.

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	1/26

Section 1. Identification of the hazardous chemical and of the supplier

Supplier : Struers ApS
Pederstrupvej 84
DK-2750 Ballerup

Telephone: +45 44 600 800

e-mail address of person responsible for this SDS : sdsquestions@struers.dk
Emergency telephone number : 999 (24/7)

Bahagian 2: Pengenalan bahaya

Klasifikasi bahan atau campuran : H412 BERBAHAYA KEPADA PERSEKITARAN AKUATIK - BAHAYA KRONIK - Kategori 3

Unsur label GHS

Kata isyarat : Tiada kata isyarat.
Pernyataan bahaya : H412 - Memudaratkan kepada hidupan akuatik dengan kesan kekal berpanjangan.
Pernyataan berjaga-jaga
Pencegahan : P273 - Elakkan pelepasan bahan ke persekitaran.
Tindakan : Tidak berkenaan.
Penyimpanan : Tidak berkenaan.
Pelupusan : P501 - Lupuskan kandungan dan bekas mengikut semua peraturan tempatan, serantau, nasional dan antarabangsa.

Bahaya lain yang tidak menyebabkan ia diklasifikasikan : Mungkin membentuk campuran habuk-udara yang boleh meletup jika tersebar.

Section 2. Hazards identification

Classification of the substance or mixture : H412 HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD - Category 3

GHS label elements

Signal word : No signal word.
Hazard statements : H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements
Prevention : P273 - Avoid release to the environment.
Response : Not applicable.
Storage : Not applicable.
Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : May form explosible dust-air mixture if dispersed.

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	2/26

Bahagian 3: Komposisi dan maklumat mengenai ramuan bahan kimia berbahaya

Bahan/Penyediaan : Campuran
Cara pengenalpastian yang lain : Tidak tersedia.

Nama Ramuan	%	Pengenal pasti
Metil metakrilat	≤0.3	CAS: 80-62-6
Benzoil peroksida	≤0.1	CAS: 94-36-0

Tidak ada ramuan tambahan, setakat yang diketahui pembekal dan dalam pemekatan yang boleh didapati, diklasifikasikan sebagai berbahaya kepada kesihatan atau persekitaran sehingga perlu dilaporkan dalam seksyen ini.

Had pendedahan pekerjaan, jika tersedia, disenaraikan dalam seksyen 8.

Section 3. Composition and information of the ingredients of the hazardous chemical

Substance/mixture : Mixture
Other means of identification : Not available.

Ingredient name	%	Identifiers
Methyl methacrylate	≤0.3	CAS: 80-62-6
dibenzoyl peroxide	≤0.1	CAS: 94-36-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Bahagian 4: Langkah-langkah pertolongan cemas

Perihalan langkah pertolongan cemas yang perlu

- Sentuhan mata** : Segera jirus mata dengan air yang banyak, sekali-sekala kedipkan mata. Periksa jika memakai kanta mata dan keluarkan jika ada. Dapatkan bantuan perubatan jika kerengsaan berlaku.
- Penyedutan** : Pindahkan mangsa ke kawasan berudara segar dan biarkan mangsa dalam keadaan rehat supaya mangsa dapat bernafas dengan selesa.
- Sentuhan kulit** : Curahkan pada kulit tercemar dengan air yang banyak. Tanggalkan pakaian dan kasut yang tercemar. Dapatkan bantuan perubatan jika gejala-gejala berlaku.
- Pengingesan** : Basuh mulut dengan air. Jika bahan telah ditelan dan orang yang mengalami dedahan sedar, berikan sedikit air untuk minum. Jangan paksa muntahan kecuali diarahkan berbuat demikian oleh kakitangan perubatan.

Simptom/kesan paling penting, akut dan tertunda

Kesan Kesihatan Akut Berpotensi

- Sentuhan mata** : Pendedahan kepada kepekatan bawaan udara melebihi had pendedahan statutori atau yang dicadangkan boleh menyebabkan kerengsaan mata.

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	3/26

Bahagian 4: Langkah-langkah pertolongan cemas

- Penyedutan** : Pendedahan kepada kepekatan bawaan udara melebihi had pendedahan statutori atau yang dicadangkan boleh menyebabkan kerengsaan hidung, tekak dan paru-paru.
- Sentuhan kulit** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Pengingesan** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Gejala-gejala/tanda-tanda lampau terdedah

- Sentuhan mata** : Gejala yang teruk boleh termasuk yang berikut:
kerengsaan
kemerahan
- Penyedutan** : Gejala yang teruk boleh termasuk yang berikut:
rengsaan saluran pernafasan
batuk
- Sentuhan kulit** : Tiada data spesifik.
- Pengingesan** : Tiada data spesifik.

Tanda rawatan perubatan segera dan rawatan khas diperlukan, jika perlu

- Nota kepada doktor** : Rawat mengikut gejala. Hubungi pakar rawatan keracunan segera jika tertelan atau tersedut dalam kuantiti yang besar.
- Rawatan spesifik** : Tiada rawatan spesifik.
- Perlindungan untuk pemberi pertolongan cemas** : Jangan lakukan sebarang tindakan yang membabitkan risiko peribadi atau tanpa latihan yang sewajarnya.

Lihat Maklumat Toksikologi (Seksyen 11)

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
- Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	4/26

Section 4. First aid measures

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Bahagian 5: Langkah-langkah pemadaman kebakaran

Media pemadam kebakaran

Media pemadam yang sesuai	: Guna serbuk bahan kimia KERING. Guna bahan kimia kering, CO ₂ , semburan air (kabut) atau busa.
Media pemadam yang tidak sesuai	: Jangan guna jet air.

Bahaya khusus yang timbul daripada bahan kimia ini :  Mungkin membentuk campuran habuk-udara yang boleh meletup jika tersebar. Bahan ini membahayakan hidupan akuaria dengan kesan yang berkekalan. Air pemadaman kebakaran yang tercemar dengan bahan ini mesti dibendung dan dielakkan daripada memasuki jalan air, pembetung atau longkang.

Hasil penguraian terma yang berbahaya : Produk penguraian mungkin termasuk bahan berikut:
oksida logam

Tindakan perlindungan khas untuk ahli bomba : Kosongkan kawasan serta-merta dengan mengeluarkan semua orang daripada kawasan sekeliling jika kebakaran berlaku. Jangan lakukan sebarang tindakan yang membabitkan risiko peribadi atau tanpa latihan yang sewajarnya. Alih bekas daripada kawasan kebakaran jika ini boleh dilakukan tanpa risiko. Guna semburan air untuk menyejukkan bekas yang terdedah kepada api.

Alat perlindungan khas untuk ahli bomba : Ahli bomba perlulah memakai peralatan perlindungan bersesuaian dan peralatan pernafasan serba lengkap dengan penutup muka penuh dalam operasi mod tekanan positif.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media	: Use dry chemical powder. Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

Tarikh keluaran/Tarikh semakan
Date of issue/Date of revision

: 20/03/2026

Tarikh Keluaran Terdahulu
Date of previous issue

: 13/01/2025
: 13/01/2025

Versi : 3
Version

5/26

Section 5. Firefighting measures

Specific hazards arising from the chemical	: May form explosible dust-air mixture if dispersed. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Bahagian 6: Langkah-langkah pelepasan tidak sengaja

Langkah berjaga-jaga peribadi, peralatan pelindung dan prosedur kecemasan

Untuk kakitangan bukan kecemasan	: Jangan lakukan sebarang tindakan yang membabitkan risiko peribadi atau tanpa latihan yang sewajarnya. Kosongkan kawasan persekitaran. Halang kakitangan tidak berkaitan dan tidak dilindungi daripada masuk. Jangan sentuh atau jalan melalui bahan tertumpah. Tutup semua sumber pencucuhan. Tiada menyala, merokok atau nyalaan di kawasan bahaya. Elakkan menyedut debu. Pakai peralatan perlindungan diri yang sesuai.
Untuk pasukan tindak balas kecemasan	: Jika pakaian khas diperlukan bagi mengendalikan tumpahan, perhatikan apa jua maklumat dalam Seksyen 8 tentang bahan yang sesuai dan tidak sesuai. Lihat juga maklumat dalam bahagian "Untuk kakitangan bukan kecemasan".
Peringatan alam sekitar	: Elakkan penyebaran bahan tertumpah dan aliran dan bersentuh dengan tanah, jalan air, longkang dan pembetung. Beritahu pihak berkuasa yang berkaitan jika produk menyebabkan pencemaran persekitaran (pembetung, aliran air, tanah atau udara). Bahan mencemar air. Boleh memudaratkan alam sekitar jika terlepas dalam jumlah yang banyak.

Kaedah dan bahan bagi pembendungan dan pembersihan

Tumpahan kecil	: Alih bekas daripada kawasan tumpahan. Gunakan alat kalis percikan dan peralatan kalis letupan. Vakum atau sapu bahan dan simpan di dalam bekas sisa label yang ditentukan. Buang melalui kontraktor pelupusan sisa yang berlesen. Serap tumpahan dengan bahan lengai (contohnya pasir atau tanah kering) dan letakkan dalam suatu bekas sisa bahan kimia.
Tumpahan besar	: Alih bekas daripada kawasan tumpahan. Gunakan alat kalis percikan dan peralatan kalis letupan. Pendekatan lepas dari arah angin bertiup jauh dari kamu, bukan ke arah kamu. Cegah kemasukan ke dalam pembetung, aliran air, basemen atau ruang terbatas. Vakum atau sapu bahan dan simpan di dalam bekas sisa label yang ditentukan. Elakkan mewujudkan keadaan berdebu dan cegah penyebaran angin. Buang melalui kontraktor pelupusan sisa yang berlesen.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	6/26

Section 6. Accidental release measures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

- Small spill** : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. Absorb spill with inert material (e.g. dry sand or earth) and place in a chemical waste container.
- Large spill** : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.

Bahagian 7: Pengendalian dan penyimpanan

Langkah berjaga-jaga bagi mengendalikan dengan selamat

- Langkah perlindungan** : Pakai kelengkapan perlindungan peribadi bersesuaian (Lihat Seksyen 8). Jangan inges. Elakkan tersentuh mata, kulit dan pakaian. Elakkan menyedut debu. Elakkan pelepasan bahan ke persekitaran. Elak pembentukan debu semasa pengendalian dan elak segala kemungkinan sumber nyalaan (cetusan api atau nyala api). Cegah pengumpulan debu. Guna hanya dengan ventilasi mencukupi. Pakai alat pernafasan yang sesuai apabila ventilasi tidak mencukupi. Simpan di dalam bekas asal atau bekas lain yang diluluskan yang diperbuat daripada bahan yang sesuai, tutup ketat apabila tidak digunakan. Peralatan elektrik dan lampu harus dilindungi mengikut piawai tertentu untuk mengelak debu daripada bersentuhan dengan permukaan panas, percikan atau sumber penyalan lain. Ambil langkah peringatan terhadap nyahcas elektrostatik. Untuk elakkan kebakaran dan letupan, singkirkan elektrostatik semasa pemindahan dengan membumikan dan mengikat bekas dan peralatan sebelum memindahkan bahan. Bekas kosong mengandungi sisa produk dan boleh menjadi berbahaya. Jangan guna semula bekas.
- Nasihat tentang aturan kebersihan pekerjaan umum** : Makan, minum dan menghisap rokok harus dilarang dalam kawasan di mana bahan ini dikendalikan, disimpan dan diproses. Para pekerja harus membasuh tangan dan muka sebelum makan, minum dan menghisap rokok. Tanggalkan pakaian yang tercemar dan peralatan perlindungan sebelum masuk tempat makan. Lihat juga Seksyen 8 untuk maklumat tambahan tentang langkah kebersihan.

Bahagian 7: Pengendalian dan penyimpanan

- Syarat-syarat bagi penyimpanan yang selamat, termasuk apa-apa ketakserasian** :
- Simpan mengikut peraturan tempatan. Simpan di dalam kawasan yang berasingan dan dibenarkan. Simpan di dalam bekas asal yang terlindung dari pancaran terus cahaya matahari dalam kawasan kering, sejuk dan pengudaraan yang baik, jauh daripada bahan tidak sesuai (lihat Seksyen 10) dan makanan dan minuman. Hapuskan semua sumber nyalaan. Asingkan daripada bahan pengoksida. Simpan bekas tertutup rapat dan terkedap sehingga sedia untuk diguna. Bekas yang telah dibuka mesti dikedap semula dengan teliti dan disimpan menegak untuk mencegah kebocoran. Jangan simpan dalam bekas tidak berlabel. Gunakan kaedah pengurungan yang sesuai untuk mengelakkan pencemaran alam sekitar. Lihat Bahagian 10 untuk bahan yang tidak serasi sebelum mengendali atau mengguna.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** :
- Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** :
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** :
- Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Bahagian 8: Kawalan pendedahan dan perlindungan diri

Parameter kawalan

Had Pendedahan Pekerja

Bahagian 8: Kawalan pendedahan dan perlindungan diri

Nama Ramuan	Had-Had Pendedahan
Metil metakrilat	Jadual I USECHH 2000 (Malaysia, 4/2000) Purata berpemberat lapan jam 8 jam: 100 ppm. Purata berpemberat lapan jam 8 jam: 410 mg/m ³ .
Benzoil peroksida	Jadual I USECHH 2000 (Malaysia, 4/2000) Purata berpemberat lapan jam 8 jam: 5 mg/m ³ .

Indeks pendedahan biologi

Tiada indeks pendedahan yang diketahui.

- Kawalan kejuruteraan yang wajar** : Guna hanya dengan ventilasi mencukupi. Jika pengendalian bahan menghasilkan debu, wasap, gas, wap atau kabut, guna penutup proses, pengalihudaraan ekzos setempat atau kawalan kejuruteraan lain untuk memastikan pekerja hanya terdedah kepada bahan cemar bawaan udara di bawah apa-apa had yang dicadangkan atau had statutori. Kawalan kejuruteraan juga perlu memastikan kepekatan gas, wap atau debu di bawah sebarang had bahan letupan yang lebih rendah. Guna peralatan ventilasi kalis letupan.
- Kawalan pendedahan alam sekitar** : Pengeluaran daripada pengudaraan atau peralatan proses kerja hendaklah diperiksa untuk memastikan ianya mematuhi keperluan perundangan perlindungan alam sekitar. Bagi sesetengah kes, penyental wasap, penuras atau pengubahsuaian kejuruteraan terhadap peralatan proses adalah perlu bagi mengurangkan pengeluaran ke tahap yang dibenarkan.

Langkah-langkah perlindungan individu

- Langkah-langkah kebersihan** : Basuh kedua tangan, lengan dan muka sehingga bersih setelah mengendalikan produk kimia, sebelum makan, merokok dan menggunakan tandas dan pada akhir waktu kerja. Teknik yang sesuai harus digunakan apabila menanggalkan pakaian yang mungkin tercemar. Basuh pakaian tercemar sebelum memakai semula. Pastikan tempat mencuci mata dan pancuran air keselamatan berdekatan dengan lokasi tempat kerja.
- Perlindungan mata/muka** : Kacamata keselamatan yang mematuhi kelulusan piawai perlu digunakan apabila penilaian risiko menunjukkan ianya perlu untuk mengelakkan pendedahan kepada percikan cecair, kabu, gas atau debu. Jika sentuhan mungkin terjadi, perlindungan berikut harus dipakai, kecuali taksiran menunjukkan tahap perlindungan lebih tinggi: cermin mata keselamatan dengan pelindung sisi. Jika keadaan pengendalian menyebabkan kepekatan debu menjadi tinggi, guna gogal debu.

Perlindungan kulit

- Perlindungan tangan** : Sarung tangan kedap penentang bahan kimia, yang mematuhi piawaian yang diluluskan hendaklah dipakai pada setiap masa apabila mengendalikan produk kimia jika penilaian risiko menunjukkan ini adalah perlu. Dengan mempertimbangkan parameter yang ditetapkan oleh pengilang sarung tangan, pastikan semasa digunakan bahawa sarung tangan masih mengekalkan ciri-ciri perlindungannya. Harus diperhatikan bahawa jangka masa hingga terobos untuk mana-mana bahan sarung tangan mungkin berbeza mengikut pengilang sarung tangan. Bagi kes campuran, yang terdiri daripada beberapa zat, jangka masa perlindungan sarung tangan tidak dapat dianggarkan dengan tepat. Disyorkan: Sarung tangan nitril. Jangka masa terobos mestilah lebih panjang daripada jangka masa kegunaan akhir produk.

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	9/26

Bahagian 8: Kawalan pendedahan dan perlindungan diri

- Perlindungan tubuh** : Peralatan perlindungan peribadi untuk badan perlu dipilih berdasarkan tugas yang dilakukan dan risiko yang terlibat dan perlulah diluluskan oleh pakar sebelum mengendalikan produk ini.
- Perlindungan kulit yang lain** : Kasut yang wajar dan apa jua langkah tambahan bagi perlindungan kulit harus dipilih berdasarkan tugas yang dilakukan dan risiko yang terbabit, dan harus diluluskan oleh seorang pakar sebelum mengendalikan produk ini.
- Perlindungan respiratori** : Berdasarkan bahaya dan kemungkinan pendedahan, pilih respirator yang memenuhi standard atau pensijilan yang sewajarnya. Respirator harus digunakan mengikut program pelindung pernafasan bagi memastikan pemakaian dan latihan yang betul, serta aspek penggunaan lain yang penting. Disyorkan: Penyaring partikel: P3

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
methyl methacrylate	Schedule I USECHH 2000 (Malaysia, 4/2000) TWA 8 hours: 100 ppm. TWA 8 hours: 410 mg/m ³ .
dibenzoyl peroxide	Schedule I USECHH 2000 (Malaysia, 4/2000) TWA 8 hours: 5 mg/m ³ .

Biological exposure indices

None known.

- Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	10/26

Section 8. Exposure controls/personal protection

Skin protection

- Hand protection** :  Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Recommended: Nitrile gloves. The breakthrough time must be greater than the end use time of the product.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: particulate filter: P3

Bahagian 9: Sifat fizikal dan kimia

Keadaan pengukuran semua sifat berada pada suhu dan tekanan standard kecuali dinyatakan sebaliknya.

Rupa

- Keadaan fizikal** : Pepejal. [Serbuk.]
- Warna** : Kelabu./ Hitam.
- Bau** : Lembut.
- Ambang Bau** : Tidak tersedia.
- pH** : Tidak tersedia.
- Takat lebur/takat beku** : Tidak tersedia.
- Takat didih, takat didih awal, dan julat didih** : Tidak tersedia.
- Takat kilat** : Tidak berkenaan.
- Kadar Penyejatan** : Tidak tersedia.
- Kemudahbakaran** : Tidak tersedia.
- Had kemudahbakaran atas/ bawah atau had letupan** : Tidak berkenaan.
- Tekanan Wap** : Tidak tersedia.
- Ketumpatan wap** : Tidak berkenaan.
- Ketumpatan bandingan** : 1.1 hingga 1.8
- Keterlarutan** :
- | Media | Keputusan |
|-------|-------------|
| air | Tidak larut |
- Boleh dicampur dengan air** : Tiada.
- Pekali sekatan: n-oktanol/air** : Tidak berkenaan.
- Suhu pengautocucuhan** : Tidak berkenaan.

Tarikh keluaran/Tarikh semakan
Date of issue/Date of revision

: 20/03/2026

Tarikh Keluaran Terdahulu
Date of previous issue

: 13/01/2025
: 13/01/2025

Versi : 3
Version

11/26

Bahagian 9: Sifat fizikal dan kimia

Suhu penguraian	: Tidak tersedia.
Kelikatan	: Dinamik (suhu bilik): Tidak bekenaan. Kinematik (suhu bilik): Tidak bekenaan. Kinematik (40°C (104°F)): Tidak bekenaan.
Masa aliran (ISO 2431)	: Tidak tersedia.
<u>Ciri-ciri zarah</u>	
Saiz zarah median	: Tidak tersedia.
<u>Maklumat lain</u>	
Catatan Fizikal Bahan Kimia	: Tiada maklumat tambahan.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Solid. [Powder.]				
Colour	: Grey./ Black.				
Odour	: Mild.				
Odour threshold	: Not available.				
pH	: Not available.				
Melting point/freezing point	: Not available.				
Boiling point or initial boiling point and boiling range	: Not available.				
Flash point	: Not applicable.				
Evaporation rate	: Not available.				
Flammability	: Not available.				
Lower and upper explosion limit/flammability limit	: Not applicable.				
Vapour pressure	: Not available.				
Relative vapour density	: Not applicable.				
Relative density	: 1.1 to 1.8				
Solubility(ies)	: <table border="1" data-bbox="516 1360 1510 1453"> <tr> <th>Media</th><th>Result</th></tr> <tr> <td>water</td><td>Not soluble</td></tr> </table>	Media	Result	water	Not soluble
Media	Result				
water	Not soluble				

Solubility in water	: Not available.
Miscible with water	: No.
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available.
Viscosity	: Dynamic (room temperature): Not applicable. Kinematic (room temperature): Not applicable. Kinematic (40°C (104°F)): Not applicable.
Flow time (ISO 2431)	: Not available.
<u>Particle characteristics</u>	
Median particle size	: Not available.

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	12/26

Section 9. Physical and chemical properties

Additional information

Physical/chemical properties comments : No additional information.

Bahagian 10: Kestabilan dan kereaktifan

Kereaktifan	: Tiada data ujian khusus berkaitan dengan kereaktifan bagi produk ini atau ramuannya.
Kestabilan bahan	: Produk ini stabil.
Kemungkinan berlakunya tindak balas berbahaya	: Dalam keadaan penyimpanan dan penggunaan yang normal, tindak balas berbahaya tidak akan terjadi. Di bawah keadaan normal penyimpanan dan penggunaan, pemolimeran berbahaya tidak akan berlaku.
Keadaan yang perlu dielak	: Elak pembentukan debu semasa pengendalian dan elak segala kemungkinan sumber nyalaan (cetus api atau nyala api). Ambil langkah peringatan terhadap nyahcas elektrostatik. Untuk elakkan kebakaran dan letupan, singkirkan elektrostatik semasa pemindahan dengan membumikan dan mengikat bekas dan peralatan sebelum memindahkan bahan. Cegah pengumpulan debu.
Bahan tidak serasi	: Reaktif atau tidak serasi dengan bahan yang berikut: bahan pengoksida
Produk penguraian berbahaya	: Di bawah keadaan penyimpanan dan penggunaan normal, produk penguraian berbahaya tidak akan terhasil.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust accumulation.

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	13/26

Section 10. Stability and reactivity

Incompatible materials : Reactive or incompatible with the following materials:
oxidising materials

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Bahagian 11: Maklumat toksikologi

Maklumat tentang kesan toksikologi

Ketoksikan akut

Nama produk/bahan

Metil metakrilat

Keputusan

Tikus - Oral - LD50
7872 mg/kg

Arnab - Kulit - LD50
>5 g/kg

Tikus - Penyedutan - LC50 Wap
29.8 mg/l [4 jam]

Tikus - Oral - LD50
6400 mg/kg

Tikus - Penyedutan - LC50 Debu dan Kabus
>24.3 mg/l [4 jam]

Kesan toksik: Tingkah laku -
Kelemahan otot Tingkah laku - Koma
Paru-paru, Toraks, atau Pernafasan -
Kemurungan pernafasan
Kesan toksik: Kulit Selepas
pendedahan sistemik - Dermatitis,
lain-lain

Benzoil peroksida

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Kakisan atau kerengsaan kulit

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Kerosakan mata yang serius/kerengsaan mata

Nama produk/bahan

Benzoil peroksida

Keputusan

Arnab - Mata - Zat merengsa ringan
Jangka masa rawatan/pendedahan: 24 jam
Jumlah/kepekatan yang diterapkan: 500 mg

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Kakisan/kerengsaan pernafasan

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Pemekaan kulit

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Bahagian 11: Maklumat toksikologi

Pemekaan pernafasan

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Mutagenitas sel kuman

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Karsinogenisiti

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Toksisiti reproduktif

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Ketoksikan organ sasaran khusus (pendedahan tunggal)

Nama produk/bahan

Metil metakrilat

Keputusan

KETOKSIKAN ORGAN SASARAN KHUSUS - PENDEDAHAN TUNGGAL (Kerengsaan saluran pernafasan) - Kategori 3

Ketoksikan organ sasaran khusus (pendedahan berulang)

Tidak tersedia.

Bahaya penyedutan

Tidak tersedia.

Maklumat tentang laluan pendedahan yang berkemungkinan

Laluan kemasukan dijangkakan: Oral, Kulit, Penyedutan, Mata.

Kesan Kesihatan Akut Berpotensi

- | | |
|----------------|--|
| Sentuhan mata | : Pendedahan kepada kepekatan bawaan udara melebihi had pendedahan statutori atau yang dicadangkan boleh menyebabkan kerengsaan mata. |
| Penyedutan | : Pendedahan kepada kepekatan bawaan udara melebihi had pendedahan statutori atau yang dicadangkan boleh menyebabkan kerengsaan hidung, tekak dan paru-paru. |
| Sentuhan kulit | : Tiada kesan yang penting atau bahaya kritikal yang diketahui. |
| Pengingesan | : Tiada kesan yang penting atau bahaya kritikal yang diketahui. |

Gejala yang berkaitan dengan ciri fizikal, kimia dan toksikologi

- | | |
|---------------|--|
| Sentuhan mata | : Gejala yang teruk boleh termasuk yang berikut:
kerengsaan
kemerahan |
| Penyedutan | : Gejala yang teruk boleh termasuk yang berikut:
kerengsaan saluran pernafasan
batuk |

Tarikh keluaran/Tarikh semakan
Date of issue/Date of revision

: 20/03/2026

Tarikh Keluaran Terdahulu
Date of previous issue

: 13/01/2025
: 13/01/2025

Versi : 3
Version

15/26

Bahagian 11: Maklumat toksikologi

Sentuhan kulit : Tiada data spesifik.

Pengingesan : Tiada data spesifik.

Kesan tertunda dan serta merta, dan juga kesan kronik akibat pendedahan jangka pendek dan panjang

Pendedahan jangka pendek

Kesan serta merta yang berpotensi : Tidak tersedia.

Kesan tertunda yang berpotensi : Tidak tersedia.

Pendedahan jangka panjang

Kesan serta merta yang berpotensi : Tidak tersedia.

Kesan tertunda yang berpotensi : Tidak tersedia.

Kesan Kesihatan Kronik Berpotensi

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Am : Pendedahan debu berulang atau berpanjangan boleh membawa kepada rensaan pernafasan yang kronik.

Karsinogenisiti : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Mutagenisiti : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Toksisiti reproduktif : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Ukuran ketoksikan secara angka

Anggaran ketoksikan akut

Nama produk/bahan	Oral (mg/kg)	Kulit (mg/kg)	Penyedutan (gas) (ppm)	Penyedutan (wap) (mg/l)	Penyedutan (habuk dan kabus) (mg/l)
Metil metakrilat	7872	N/A	N/A	29.8	N/A
Benzoil peroksida	6400	N/A	N/A	N/A	N/A

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result
-------------------------	--------

Section 11. Toxicological information

 methyl methacrylate

Rat - Oral - LD50

7872 mg/kg

Rabbit - Dermal - LD50

>5 g/kg

Rat - Inhalation - LC50 Vapour

29.8 mg/l [4 hours]

Rat - Oral - LD50

6400 mg/kg

Rat - Inhalation - LC50 Dusts and mists

>24.3 mg/l [4 hours]

Toxic effects: Behavioral - Muscle weakness Behavioral - Coma Lung, Thorax, or Respiration - Respiratory depression

Toxic effects: Skin After systemic exposure - Dermatitis, other

dibenzoyl peroxide

Conclusion/Summary [Product] : Not available.

Skin irritation/corrosivity

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

 dibenzoyl peroxide

Result

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Conclusion/Summary [Product] : Not available.

Skin sensitisation

Conclusion/Summary [Product] : Not available.

Respiratory sensitisation

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Conclusion/Summary [Product] : Not available.

<i>Tarikh keluaran/Tarikh semakan</i>	: 20/03/2026	<i>Tarikh Keluaran Terdahulu</i>	: 13/01/2025	<i>Versi</i>	: 3
<i>Date of issue/Date of revision</i>		<i>Date of previous issue</i>	: 13/01/2025	<i>Version</i>	17/26

Section 11. Toxicological information

Reproductive toxicity

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

Methyl methacrylate

Result

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

- Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
- Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

<i>Tarikh keluaran/Tarikh semakan</i>	: 20/03/2026	<i>Tarikh Keluaran Terdahulu</i>	: 13/01/2025	<i>Versi</i>	: 3
<i>Date of issue/Date of revision</i>		<i>Date of previous issue</i>	: 13/01/2025	<i>Version</i>	18/26

Section 11. Toxicological information

Potential chronic health effects

Conclusion/Summary [Product] : Not available.

General : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
methyl methacrylate	7872	N/A	N/A	29.8	N/A
dibenzoyl peroxide	6400	N/A	N/A	N/A	N/A

Bahagian 12: Maklumat ekologi

Ketoksikan

Nama produk/bahan

Metil metakrilat

Keputusan

Akut - LC50 - Air tawar

Ikan - Fathead minnow - *Pimephales promelas* - Dewasa
130 mg/l [96 jam]

Akut - EC50 - Air tawar

Alga
>110 mg/l [72 jam]

Benzoil peroksida

Akut - LC50 - Air tawar

Ikan - *Oncorhynchus mykiss*
0.06 mg/l [96 jam]

Akut - EC50 - Air tawar

Dafnia - *Daphnia magna*
0.11 mg/l [48 jam]

Akut - EC50 - Air tawar

Alga
0.042 mg/l [72 jam]

Akut - NOEC - Air tawar

Alga
0.02 mg/l [72 jam]

Kronik - NOEC - Air tawar

Dafnia - *Daphnia magna*
0.001 mg/l [21 hari]

Kesan: Kematian

EPA 201 [Alga, Ujian Perencatan Pertumbuhan]

OECD 203 [Ikan, Ujian Ketoksikan Akut]

OECD 202 [Daphnia sp. Ujian Imobilisasi Akut dan Ujian Pembiakan]

OECD 201 [Alga, Ujian Perencatan Pertumbuhan]

OECD 201 [Alga, Ujian Perencatan Pertumbuhan]

OECD 211 [Ujian Pembiakan Daphnia Magna]

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	19/26

Bahagian 12: Maklumat ekologi

Kegigihan dan degradasi

Nama produk/bahan

Benzoil peroksida

Keputusan

Aerobik

71% [28 hari] - Dengan mudah

OECD 301D [Kebolehiodegradasi
sedia - Ujian Botol Tertutup]

Kesimpulan/Ringkasan[Produk] : Tidak tersedia.

Nama produk/bahan	Separuh hayat Akuatik	Fotolisis	Sifat biorosot
CONDUFAST	-	-	Tidak mudah
Metil metakrilat	-	-	Dengan mudah
Benzoil peroksida	-	-	Dengan mudah

Potensi bioakumulasi

Nama produk/bahan	LogP _{ow}	BCF	Berpotensi
Metil metakrilat	1.38	-	Rendah
Benzoil peroksida	3.2	-	Rendah

Mobiliti tanah

Pekali Sekatan Tanah/Air : Tidak tersedia.

Kesan-kesan buruk lain

Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Section 12. Ecological information

Toxicity

Product/ingredient name

Methyl methacrylate

Result

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales
promelas* - Adult

130 mg/l [96 hours]

Acute - EC50 - Fresh water

Algae

>110 mg/l [72 hours]

Acute - LC50 - Fresh water

Fish - *Oncorhynchus mykiss*

0.06 mg/l [96 hours]

Acute - EC50 - Fresh water

Daphnia - *Daphnia magna*

0.11 mg/l [48 hours]

Acute - EC50 - Fresh water

Algae

0.042 mg/l [72 hours]

Acute - NOEC - Fresh water

Algae

0.02 mg/l [72 hours]

Chronic - NOEC - Fresh water

Daphnia - *Daphnia magna*

0.001 mg/l [21 days]

Effect: Mortality

EPA 201 [Alga, Growth Inhibition Test]

OECD 203 [Fish, Acute Toxicity Test]

OECD 202 [Daphnia sp. Acute
Immobilization Test and Reproduction
Test]

OECD 201 [Alga, Growth Inhibition
Test]

OECD 201 [Alga, Growth Inhibition
Test]

OECD 211 [Daphnia Magna
Reproduction Test]

dibenzoyl peroxide

Tarikh keluaran/Tarikh semakan

: 20/03/2026

Tarikh Keluaran Terdahulu

: 13/01/2025

Versi : 3

Date of issue/Date of revision

Date of previous issue

: 13/01/2025

Version

20/26

Section 12. Ecological information

Conclusion/Summary [Product] : Not available.

Persistence and degradability

Product/ingredient name

Result

dibenzoyl peroxide

Aerobic
71% [28 days] - Readily

OECD 301D [Ready Biodegradability -
Closed Bottle Test]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
CONDUFAST	-	-	Not readily
methyl methacrylate	-	-	Readily
dibenzoyl peroxide	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
methyl methacrylate	1.38	-	Low
dibenzoyl peroxide	3.2	-	Low

Mobility in soil

Soil/water partition coefficient : Not available.

Other adverse effects

No known significant effects or critical hazards.

Bahagian 13: Maklumat pelupusan

Kaedah pelupusan : Penghasilan sisa perlulah dielakkan atau diminimumkan sekiranya boleh. Pelupusan produk ini, larutan dan sebarang produk sampingan perlulah pada setiap masa mematuhi keperluan perlindungan alam sekitar dan perundangan pelupusan sisa dan sebarang keperluan pihak berkuasa serantau tempatan. Pembuangan lebihan dan hasilan yang tidak boleh dikitar semula melalui kontraktor pelupusan sisa yang berlesen. Bahan buangan tidak harus dibuang secara tidak dirawat ke pembentung kecuali patuh sepenuhnya kepada keperluan semua pihak berkuasa dengan kuasa undang-undang. Bungkusan buangan harus dikitar semula. Penunuan atau kabus tanah hanya harus dipertimbangkan apabila tidak mungkin dikitar semula. Bahan ini dan bekasnya hendaklah dilupuskan dengan cara yang selamat. Hati-hati apabila mengendalikan bekas yang telah dikosongkan tetapi belum dibersihkan atau dibilas. Bekas atau pelapik kosong mungkin mengandungi sisa-sisa produk. Elakkan penyebaran bahan tertumpah dan aliran dan bersentuh dengan tanah, jalan air, longkang dan pembetung.

Section 13. Disposal information

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	21/26

Section 13. Disposal information

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Bahagian 14: Maklumat pengangkutan

	UN	ADR/RID	IMDG	IATA
Nombor UN	Tidak dikawal.	Tidak dikawal.	Not regulated.	Not regulated.
Nama penghantaran sah PBB	-	-	-	-
Kelas bahaya pengangkutan	-	-	-	-
Kumpulan Pembungkusan	-	-	-	-
Bahaya Alam Sekitar	Tiada.	Tiada.	No.	No.

Langkah pencegahan istimewa untuk pengguna : "Pengangkutan dalam premis pemilik:" sentiasa mengangkut dalam bekas bertutup yang tegak dan selamat. Pastikan orang yang mengangkut produk tahu apa yang perlu dilakukan sekiranya berlaku kemalangan atau tumpahan.

Angkut secara pukal menurut alatan IMO : Tidak tersedia.

Section 14. Transport information

	UN	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	22/26

Section 14. Transport information

Environmental hazards	No.	No.	No.	No.
-----------------------	-----	-----	-----	-----

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Bahagian 15: Maklumat pengawalseliaan

Peraturan kebangsaan

Skim Pemberitahuan & Pendaftaran Bahan Berbahaya Alam Sekitar

Tidak ditentukan

Akta Racun, Senarai Racun - Jadual 1

	Bahagian I				Bahagian II	Dikecualikan
Nama Ramuan	Kumpulan A	Kumpulan B	Kumpulan C	Kumpulan D		
minerals; the following, unless specified elsewhere in the list	-	-	Tersenarai	-	-	Pengecualian mungkin berlaku

Akta Racun, Senarai Racun - Jadual 3

Tidak berkenaan.

Peraturan Antarabangsa

Bahan Kimia Jadual I, II & III Senarai Konvensyen Senjata Kimia

Tidak tersenarai.

Protokol Montreal

Tidak tersenarai.

Konvensyen Stockholm tentang zat pencemar organik gigih

Tidak tersenarai.

Konvensyen Rotterdam tentang Izin Bermaklum Sebelumnya (PIC)

Tidak tersenarai.

Protokol UNECE Aarhus tentang POP dan Logam Berat

Tidak tersenarai.

Section 15. Regulatory information

National regulations

EHS Register

Not determined

Poison Act, Poison List - Schedule 1

<i>Tarikh keluaran/Tarikh semakan</i>	: 20/03/2026	<i>Tarikh Keluaran Terdahulu</i>	: 13/01/2025	<i>Versi</i>	: 3
<i>Date of issue/Date of revision</i>		<i>Date of previous issue</i>	: 13/01/2025	<i>Version</i>	23/26

Section 15. Regulatory information

	Part I				Part II	Exempt
Ingredient name	Group A	Group B	Group C	Group D		
minerals; the following, unless specified elsewhere in the list	-	-	Listed	-	-	Exemption may apply

Poison Act, Poison List - Schedule 3

Not applicable.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Bahagian 16: Maklumat lain

Sejarah

Tarikh keluaran/Tarikh semakan : 20/03/2026

Tarikh Keluaran Terdahulu : 13/01/2025

Versi : 3

Petunjuk untuk Singkatan : ADR = Persetujuan Eropah mengenai Pengangkutan Antarabangsa Barang-barang Berbahaya dengan Jalan
 ATE = Anggaran Keracunan Teruk
 BCF = Faktor Biokepekatan
 GHS = Sistem Global Berharmoni bagi Pengelasan dan Pelabelan Kimia
 IATA = Persatuan Pengangkutan Udara Antarabangsa
 IBC = Bekas Pukul Sederhana
 IMDG = Barang-barang Berbahaya Laut Antarabangsa
 LogPow = Logaritma pekali sekatan bagi oktanol/air
 MARPOL = Persidangan Antarabangsa bagi Pencegahan Pencemaran Daripada Kapal-kapal, 1973 seperti yang diubah oleh Protokol 1978. ("Marpol" = pencemaran laut)
 N/A = Tiada
 RID = Peraturan-peraturan mengenai Pengangkutan Antarabangsa Barang-barang Berbahaya oleh Keretapi
 SGG = Kumpulan Pengasingan
 UN = Pertubuhan Bangsa-bangsa Bersatu

Prosedur yang digunakan untuk memperoleh pengelasan

Klasifikasi	Justifikasi
BERBAHAYA KEPADA PERSEKITARAN AKUATIK - BAHAYA KRONIK - Kategori 3	Kaedah pengiraan

Tarikh keluaran/Tarikh semakan : 20/03/2026	Tarikh Keluaran Terdahulu : 13/01/2025	Versi : 3
Date of issue/Date of revision	Date of previous issue : 13/01/2025	Version 24/26

Bahagian 16: Maklumat lain

Rujukan : Industry Code of Practice on Chemical Classification and Hazard Communication 2013 (ICOP) - Section 37 of OSHA 1994
Occupational Safety and Health (Classification, Labeling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 [P.U. (A) 310/2013]
Occupational Safety and Health Act 1994 - Use and Standards of Exposure of Chemicals Hazardous to Health, USECHH) Regulations 2000, dated 29 March 2000.
The List of Permissible Exposure Limits is Schedule I (Regulations 6 and 7)
Peraturan pengangkutan antarabangsa

➤ Menunjukkan maklumat yang telah berubah daripada versi isu terdahulu.

Notis kepada pembaca

Pada pengetahuan terbaik kami, maklumat yang terkandung di dalam adalah tepat. Bagaimanapun, pembekal yang dinamakan di atas atau sebarang anak syarikatnya tidak bertanggungjawab terhadap ketepatan atau kelengkapan maklumat yang terkandung di dalam.

Penentuan terakhir kesesuaian sebarang bahan adalah tanggungjawab pengguna. Semua bahan mungkin mengandungi bahaya yang tidak diketahui dan harus digunakan dengan berhati-hati. Walaupun bahaya tertentu telah diterangkan di sini, kami tidak memberi jaminan bahawa hanya bahaya ini sahaja yang wujud.

Section 16. Other information

History

Date of issue/Date of revision : 20/03/2026

Date of previous issue : 13/01/2025

Version : 3

Key to abbreviations : ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
SGG = Segregation Group
UN = United Nations

Procedure used to derive the classification

Classification	Justification
HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD - Category 3	Calculation method

References : Industry Code of Practice on Chemical Classification and Hazard Communication 2013 (ICOP) - Section 37 of OSHA 1994
Occupational Safety and Health (Classification, Labeling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 [P.U. (A) 310/2013]
Occupational Safety and Health Act 1994 - Use and Standards of Exposure of Chemicals Hazardous to Health, USECHH) Regulations 2000, dated 29 March 2000.
The List of Permissible Exposure Limits is Schedule I (Regulations 6 and 7)

Tarikh keluaran/Tarikh semakan	: 20/03/2026	Tarikh Keluaran Terdahulu	: 13/01/2025	Versi	: 3
Date of issue/Date of revision		Date of previous issue	: 13/01/2025	Version	25/26

Section 16. Other information

International transport regulations

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.