

SAFETY DATA SHEET

LEVOCIT LIQUID

Section 1. Identification

Product identifier : LEVOCIT LIQUID
Cat. No. : 40200094, 50209100
Container size : 300 ml, 1 l
Other means of identification : Not available.
Product type : Liquid.

Recommended use of the chemical and restrictions on use

Product use : For embedding of materialographic specimens
Area of application : Professional applications.

Supplier's details : Struers ApS
Pederstrupvej 84
DK-2750 Ballerup

Telephone: +45 44 600 800

e-mail address of person responsible for this SDS : sdsquestions@struers.dk


Emergency telephone number (with hours of operation) : +45 44 600 800 (Only during office hours)

Section 2. Hazards identification

Classification of the substance or mixture	: H225	FLAMMABLE LIQUIDS - Category 2
	: H315	SKIN IRRITATION - Category 2
	: H319	EYE IRRITATION - Category 2A
	: H317	SKIN SENSITISATION - Category 1
	: H335	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3
	: H402	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3

GHS label elements

Hazard pictograms



Signal word : Danger



Section 2. Hazards identification

Hazard statements	: H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H402 - Harmful to aquatic life.
<u>Precautionary statements</u>	
Prevention	: P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P261 - Avoid breathing vapour. P264 + P265 - Wash hands thoroughly after handling. Do not touch eyes. P272 - Contaminated work clothing should not be allowed out of the workplace.
Response	: P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P317 - If skin irritation or rash occurs: Get medical help. P332 + P317 - If skin irritation occurs: Get medical help. P362 + P364 - Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P317 - If eye irritation persists: Get medical help. P319 - Get medical help if you feel unwell.
Storage	: P405 - Store locked up. P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

Ingredient name	%	Identifiers
 methyl methacrylate tetramethylene dimethacrylate	$\geq 50 - \leq 75$ $\geq 2.5 - \leq 10$	CAS: 80-62-6 CAS: 2082-81-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.



Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary



Section 4. First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".



Section 6. Accidental release measures

Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Absorb spill with inert material (e.g. dry sand or earth) and place in a chemical waste container.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Storage temperature: 10 to 25°C (50 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.



Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Methyl methacrylate	ACGIH TLV (United States, 1/2025) A4. Skin sensitiser. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm.

Biological exposure indices

No exposure indices known.

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
 Recommended: Butyl rubber gloves. nitrile rubber
 Breakthrough time: 60 minutes
 thickness: 0.3 mm
 Breakthrough time: 10 minutes
 thickness: 0.11 mm



Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A)

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid.
- Colour** : Colourless.
- Odour** : Ester.
- Odour threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : 101°C (213.8°F)
- Flash point** : Closed cup: 10°C (50°F)
- Evaporation rate** : Not available.
- Flammability** : Not available.
- Lower and upper explosion limit/flammability limit** : Lower: 2.1%
Upper: 12.5%
- Vapour pressure** : 4.7 kPa (35.253 mm Hg)
- Relative vapour density** : Not available.
- Relative density** : 0.9
- Solubility(ies)** :
- | Media | Result |
|-------|-------------|
| water | Not soluble |
- Miscible with water** : No.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : 365°C (689°F)
- Decomposition temperature** : Not available.
- SAPT** : 55°C (131°F)
- Viscosity** : Dynamic (room temperature): Not available.
Kinematic (room temperature): 3.1 mm²/s (3.1 cSt)
Kinematic (40°C (104°F)): Not available.



Section 9. Physical and chemical properties and safety characteristics

Flow time (ISO 2431)	: Not available.
<u>Particle characteristics</u>	
Median particle size	: Not applicable.
<u>Other information</u>	
Physical/chemical properties comments	: No additional information.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable. (SAPT = Self-Accelerating Polymerization Temperature: 55 °C)
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	:  Reactive or incompatible with the following materials: oxidising materials, peroxides
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	
 methyl methacrylate	Rat - Oral - LD50 7872 mg/kg	<u>Toxic effects</u> : Behavioral - Muscle weakness Behavioral - Coma Lung, Thorax, or Respiration - Respiratory depression
	Rabbit - Dermal - LD50 >5 g/kg	<u>Toxic effects</u> : Skin After systemic exposure - Dermatitis, other
	Rat - Inhalation - LC50 Vapour 78000 mg/m ³ [4 hours]	
	Rat - Inhalation - LC50 Vapour 7093 ppm [4 hours]	
tetramethylene dimethacrylate	Rat - Oral - LD50 >5000 mg/kg	



Section 11. Toxicological information

Conclusion/Summary[Product] : Not available.

Skin corrosion/irritation

Conclusion/Summary[Product] : Not available.

Serious eye damage/eye irritation

Conclusion/Summary[Product] : Not available.

Respiratory corrosion/irritation

Conclusion/Summary[Product] : Not available.

Respiratory or skin sensitization

Skin

Conclusion/Summary[Product] : Not available.

Respiratory

Conclusion/Summary[Product] : Not available.

Germ cell mutagenicity

Conclusion/Summary[Product] : Not available.

Carcinogenicity

Conclusion/Summary[Product] : Not available.

Reproductive toxicity

Conclusion/Summary[Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

 methyl methacrylate

Result

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE
(Respiratory tract irritation) - Category 3

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard



Section 11. Toxicological information

Not available.

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: May cause respiratory irritation.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Conclusion/Summary[Product] : Not available.

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Numerical measures of toxicity



Section 11. Toxicological information

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
methyl methacrylate	7872	N/A	N/A	78	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name

 methyl methacrylate

Result

Acute - LC50 - Fresh water

Fish - Bluegill - *Lepomis macrochirus* - Juvenile (Fledgling, Hatchling, Weanling)

Size: 3.65 cm; Weight: 0.9 g
191 mg/l [96 hours]

Acute - EC50 - Fresh water

Daphnia - *Daphnia magna*
69 mg/l [48 hours]

Acute - NOEC

Fish - *Oncorhynchus mykiss*
40 mg/l [96 hours]

Chronic - NOEC - Fresh water

Daphnia - *Daphnia magna*
5.09 mg/l [21 days]

Acute - EC50 - Fresh water

Algae - *Desmodesmus subspicatus*
4.97 mg/l [72 hours]

Acute - NOEC - Fresh water

Algae - *Desmodesmus subspicatus*
2.11 mg/l [72 hours]

Effect: Mortality

ISO

OECD 211 [Daphnia Magna Reproduction Test]

OECD 201 [Alga, Growth Inhibition Test]

OECD 201 [Alga, Growth Inhibition Test]

tetramethylene dimethacrylate

Conclusion/Summary[Product]

: Not available.

Persistence and degradability

Product/ingredient name

 tetramethylene dimethacrylate

Result

Aerobic

84% [28 days] - Readily

OECD 310 [Ready Biodegradability - CO2 in Sealed Vessels (Headspace Test)]

Conclusion/Summary[Product]

: Not available.



Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
methyl methacrylate	-	-	Readily
tetramethylene	-	-	Readily
dimethacrylate			

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
methyl methacrylate	1.38	-	Low
tetramethylene	3.1	-	Low
dimethacrylate			

Mobility in soil

Soil/water partition coefficient : Not available.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
UN number	UN1247	UN1247	UN1247
UN proper shipping name	METHYL METHACRYLATE MONOMER, STABILIZED	METHYL METHACRYLATE MONOMER, STABILIZED	Methyl methacrylate monomer, stabilized
Transport hazard class(es)	3 	3 	3 
Packing group	II	II	II



Section 14. Transport information

Environmental hazards	No.	No.	No.
-----------------------	-----	-----	-----

Additional information

UN : **Special provisions** 386
IMDG : **Emergency schedules** F-E, S-D
Special provisions 386
IATA : **Quantity limitation** Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353.
Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities -
Passenger Aircraft: 1 L. Packaging instructions: Y341.
Special provisions A209

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

History

Date of issue/Date of revision : 2026/03/20
Date of previous issue : 2025/01/13
Version : 1.05
Prepared by : Sphera Solutions



Section 16. Other information

Key to abbreviations

- : ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- IMO = International Maritime Organization
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- SGG = Segregation Group
- UN = United Nations

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITISATION - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3	Calculation method
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3	Calculation method

References

- : GHS - Globally Harmonised System of Classification and Labelling of Chemicals - Version : 9.
- International transport regulations

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

